

**CASE *ii***

***JXT SERIES TRACTORS***



**NORTHMEC**  
Established 1869

**Hectare per Hectare – Your Best Choice.**

	JXT55 2WD	JXT75 2/4WD
<b>ENGINE</b>	IVECO Series 8000	IVECO Series 8000
Number of cylinders	3 CYL NA	4 CYL NA
Displacement (cm <sup>3</sup> )	2931	3908
(* Power (HP/kW) @ 2500 rpm	55 HP/40 kW	75 HP/55 kW
(* Max torque (Nm) @ .... rpm / TBU %	202 Nm @ 1500 rpm / 26.7%	258 @ 1500 rpm / 18.5%
<b>TRANSMISSION</b>		
Transmission clutch	Mechanical	Mechanical
Total no. o fspeeds	8 forward, 2 reverse	8 forward, 2 reverse
Gearbox features	Constant mesh	Constant mesh
<b>PTO</b>		
PTO features	Fully independent	Fully independent
PTO speeds	540 rpm	540 rpm
<b>HYDRAULICS</b>		
Centre system (close/open)	Open	Open
Max flow output (L/min) / Max pressure (BAR)	34.0 L/min, 190 BAR	34.0 L/min, 190 BAR
<b>HYD. POWER LIFT &amp; 3 POINT LINKAGE</b>		
Control system	Mechanical	Mechanical
Control features (Position, Draft etc)	Position / Draft / Mix	Position / Draft / Mix
Draft Control	Top link	Top link
Max load capability at ball end W/horizon.links	std. 1535 kg / opt. 2155 kg	std. 1525 kg / opt. 2155 kg
<b>2WD FRONT AXLE</b>		
Axle Type	Inverted U section	Inverted U section
Adjustable tread dimension (mm)	From 1400 mm to 1900 mm	From 1440 mm to 1900 mm
Minimum turning radius without braking	3.5m	3.6m
<b>4WD FRONT AXLE</b>		
Position axle pivoting point	Coaxial	Coaxial
Adjustable tread dimension (mm)	From 1445 mm to 1875 mm	From 1445 mm to 1875 mm
Min. turning radius W/O braking & W/4WD disengaged	4.10 m	4.26 m
<b>REAR AXLE</b>		
Axle description	Flange type	Flange type
Adjustable tread dimension (mm)	From 1430 mm to 2000 mm	From 1430 mm to 2000 mm
<b>DIMENSION &amp; WEIGHT</b>		
Wheelbase 2WD (mm)	2050 mm	2200 mm
Wheelbase 4WD (mm)		2160 mm
Shipping weight	2155 kg	2482 kg
Shipping weight		2900 kg
Ground clearance 2WD (mm)	Front Wheel loaded radius - 200 mm	Front Wheel loaded radius - 200 mm
Ground clearance 4WD (mm)		Front Wheel loaded radius - 135 mm
Ground clearance rear (mm)	Rear Wheel loaded radius - 129 mm	Rear Wheel loaded radius - 129 mm
Height, centre rear axle to top ROPS	1650 mm	1650 mm
Tyre Size	2WD - Front 2WD - Back	7.50-16 16.9-30
	4WD - Front 4WD - Back	11.2-24 16.9-30

Tindrum 7/159

**⚠ Safety never hurts!** Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly.

Case IH is registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. © 2007 CNH America LLC.

Availability of some models and equipment builds varies according to the country in which the equipment is used.



**Hectare per Hectare - Your Best Choice.**

Tel: 011-9222 300 · Fax: 011-9222 358 · [www.northmec.co.za](http://www.northmec.co.za)