

TT



NEW HOLLAND

New Holland TT Tractors / Trekkers

Models / Modelle TT55 & TT75



Modern • Dynamic • Innovative
Modern • Dynamies • Innoverend

RSA SPECIFICATIONS
RSA SPESIFIKASIES

MODEL	TT55	TT75	MODEL
ENGINE	8035.05.700	8045.05.700	ENJIN
Make	IVECO	IVECO	Fabrikaat
Emmission Level (TIER)	1	1	Model
Number of cylinders	3	4	Aantal silinders
Aspiration	Natural	Natural	Aspirasie
Displacement (cm3)	2,931	3,908	Verplasing
Bore x Stroke (mmxmm)	104 x 115	104 x 115	Boor en Slag
Rated Speed (rpm)	2,500	2,500	Aangeslane Spoed
Air Cleaner Type	Dry Type	Dry Type	Lugfiltreer Tipe
Rated Power ISOTR14396 (kW / BHp)	42 / 55	55 / 75	Aangeslane Krag ISOTR14396 (kW / BHp)
ISO Max Torque (Nm@Rpm)	202@1500	258@1500	ISO Maksimum Wringkrag (Nm@Rpm)
Torque Rise (%)	27%	19%	Wringkrag Reserve
PTO Power kW @ Rated Speed Rpm	38.2@1500	50.3@1500	KAT krag @ Aangeslane Spoed
Fuel Consumption @ Rated Speed (g/kWh@Kg/h)	225	224	Brandstofverbruik @ Aangeslane Spoed (g/kWh@Kg/h)
Block Type	Dry Liner	Dry Liner	Blok Tipe
TRANSMISSION			TRANSMISSIE
Constant Mesh	8 F x 2 R Partially Synchronized		Constant Mesh
Option	-	12 F x 3 R CREEPER	Opsie
Speed Range (30kph / 40kph)	30		Spoed (30kpu / 40kpu)
PTO	Fully Independent 540@1980rpm		KAT-koppelaar
BRAKES	Oil Immersed , Multi Disc , Sealed , Mechanically Actuated		REMME
ELECTRICAL SYSTEM			ELEKTRIESE STELSEL
Voltage	12 Volt		Spanning
HYDRAULICS / LIFT			HIDROULIES / HYSER
Open / Closed Centre Remote Valves	Open Centre Hydraulic Valves		Oop / Geslote Baan Beheer Kleppe
Control Valves Standard	1 x Single, Double Acting		Beheerklap Standaard
Control Valves Optional (* Local Fit)	-		Beheerklap Opsioneel
Nominal system pressure(bar)	190		Pomp druk (bar)
Hydraulic pump	Gear Type		Hidroulise pomp
Pump capacity (l/m)	34		Pomplewering (l/m)
Hitch (3-point)	Cat / Kat I / II		Driepunthaak
Lift Capacity At Ball Ends (kg) 610mm	1,530	1,650	Hysvermoë by Bal Ente (kg) 610mm
Draft sensing	Top Link		Trek-en posisiebeheer
Programmable Features	Lift 'o Matic	Lift 'o Matic	Programmeerbare Funksies
CAPACITIES			KAPASITEIT
Fuel Tank Capacity (litres)	60		Brandstoftenk (Liter)
STEERING SYSTEM			STUURSTELSEL
Type	Hydrostatic	Hydrostatic	Tipe
Pump	Dedicated	Dedicated	Pomp
Turning radius (w/o brakes) 2WD (mm)	3,500	3,600	Draaisirkel Sonder Remme 2WD (mm)
Turning radius (w/o brakes) 4WD (mm)	-	4,260	Draaisirkel Sonder Remme 4WD (mm)
OPERATORS ENVIRONMENT			OPERATEURS OMGEWING
Grammar Seat	Standard	Standard	"Grammar" Sitplek
Safety Frame			Veiligheids Raam
Canopy	Standard	Standard	Sondakkie
Roll Over Protection System (R.O.P.S.)	Standard		Omrol Beskermings Stelsel (R.O.P.S.)
MASS (Unballasted kg)			MASSA (Sonder belading kg)
2WD	2,290	2,415	2WD
4WD	-	2,630	4WD
Ballast			Belading
Front (Standard / Maximum) kg	175 / 370	190 / 370	Voor (Standaard / Maksimum) kg
Rear (Standard / Maximum) kg	0 / 220	220 / 340	Agter (Standaard / Maksimum) kg
DIMENSIONS			AFMETINGS
Overall Length			Lengte
2WD (mm)	2,900	3,830	2WD (mm)
4WD (mm)	-	3,830	4WD (mm)
Height, Top of ROPS or Safety Frame (mm)	2,270	2,580	Hoogte-bokant van ROPS (mm)
Wheelbase			Asafstand
2WD (mm)	2,050	2,210	2WD (mm)
4WD (mm)	-	2,160	4WD (mm)
Ground Clearance (mm) 2WD / 4WD	430 / -	500 / 405	Grondvryhoogte-Voor As 4WD (mm)
Track Width (Cen to Cen) Min. / Max. 2WD Front	1,400 / 1,900 mm		Spoor Wydte (Mid tot Mid) Min. / Maks. 2WD Voor
Track Width (Cen to Cen) Min. / Max. 2WD Rear	1,430 / 2,000 mm		Spoor Wydte (Mid tot Mid) Min. / Maks. 2WD Agter
Track Width (Cen to Cen) Min. / Max. 4WD Front	-	1,445 / 1,875 mm	Spoor Wydte (Mid tot Mid) Min. / Maks. 4WD Voor
Track Width (Cen to Cen) Min. / Max. 4WD Rear	-	1,400 / 2,000 mm	Spoor Wydte (Mid tot Mid) Min. / Maks. 4WD Agter
Tyres			Bande
Interaxial Ratio	n/a	n/a	Inter-as Verhouding
2WD Front Standard	7.50 x 16"	7.50 x 16"	2WD Voor Standaard
4WD Front Standard	-	12.4 x 24"	4WD Voor Standaard
2WD Rear Standard	16.9 x 28"	16.9 x 30"	2WD Agter Standaard
4WD Rear Standard	-	16.9 x 30"	4WD Agter Standaard

PRINT 2000 ☎ (011) 893-3255


NEW HOLLAND

 Please consult your New Holland Dealer as these specifications may change without prior notice
 Kontak u New Holland Handelaar om spesifikasies te bevestig aangesien spesifikasies sonder voorafkenningsgewing kan verander

www.nhsa.co.za Tel 011 922 2300